

Cubo Outdoor Cabinet



**Strong as steel
for demanding
outdoor use.**

Casemet Cubo OC is an excellent enclosure solution for protecting electrical technology and hydraulics in demanding conditions. Cubo OC has been specially developed for outdoor use, such as rail or road-side transport.

The two-door cabinet is available with ratings IP55 and IK10, in sizes 1200x1000x500 - 1800x1800x600. The one-door cabinet is available with ratings IP65 and IK10, in sizes 600x1000x400 - 1000x1800x600.

Customized solutions available as well.



Conformity

Cabinets



Technical information

Degree of protection IP65/55

Impact resistance IK10 (-25°C... +35°C)

Material

Base/door Aluminum (3mm), stainless steel AISI304 (2mm), stainless steel AISI316L (2mm), galvanized steel (2mm)

Gasket
Hinges
Lock

Silicone
Stainless steel
Locking rods

Casemet Cubo OC -cabinets, 1-door

OCAL/OCSS/OCAS/OCAZ 6010040	600	1000	400
OCAL/OCSS/OCAS/OCAZ 6012040	600	1200	400
OCAL/OCSS/OCAS/OCAZ 6014040	600	1400	400
OCAL/OCSS/OCAS/OCAZ 6016050	600	1600	500
OCAL/OCSS/OCAS/OCAZ 6018050	600	1800	500
OCAL/OCSS/OCAS/OCAZ 8010050	800	1000	500
OCAL/OCSS/OCAS/OCAZ 8012050	800	1200	500
OCAL/OCSS/OCAS/OCAZ 8014050	800	1400	500
OCAL/OCSS/OCAS/OCAZ 8016050	800	1600	500
OCAL/OCSS/OCAS/OCAZ 8018050	800	1800	500
OCAL/OCSS/OCAS/OCAZ 10010050	1000	1000	500
OCAL/OCSS/OCAS/OCAZ 10012050	1000	1200	500
OCAL/OCSS/OCAS/OCAZ 10014050	1000	1400	500
OCAL/OCSS/OCAS/OCAZ 10016060	1000	1600	600
OCAL/OCSS/OCAS/OCAZ 10018060	1000	1800	600
OCAL/OCSS/OCAS/OCAZ 12010050	1200	1000	500
OCAL/OCSS/OCAS/OCAZ 12012060	1200	1200	600
OCAL/OCSS/OCAS/OCAZ 12014060	1200	1400	600

Casemet Cubo OC -cabinets, 2-door

OCAL/OCSS/OCAS/OCAZ 12010050D	1200	1000	500
OCAL/OCSS/OCAS/OCAZ 12012050D	1200	1200	500
OCAL/OCSS/OCAS/OCAZ 12014050D	1200	1400	500
OCAL/OCSS/OCAS/OCAZ 12016060D	1200	1600	600
OCAL/OCSS/OCAS/OCAZ 12018060D	1200	1800	600
OCAL/OCSS/OCAS/OCAZ 14010060D	1400	1000	600
OCAL/OCSS/OCAS/OCAZ 14012060D	1400	1200	600
OCAL/OCSS/OCAS/OCAZ 14014060D	1400	1400	600
OCAL/OCSS/OCAS/OCAZ 14016060D	1400	1600	600
OCAL/OCSS/OCAS/OCAZ 14018060D	1400	1800	600
OCAL/OCSS/OCAS/OCAZ 16014060D	1600	1400	600
OCAL/OCSS/OCAS/OCAZ 16016060D	1600	1600	600
OCAL/OCSS/OCAS/OCAZ 16018060D	1600	1800	600
OCAL/OCSS/OCAS/OCAZ 18016060D	1800	1600	600
OCAL/OCSS/OCAS/OCAZ 18018060D	1800	1800	600

OCAL = material 3 mm aluminum EN AW 5754 H22
 OCSS = material 2 mm stainless steel AISI304
 OCAS = material 2 mm stainless steel AISI316L
 OCAZ = material 2 mm galvanized steel DX51D+Z275MBC
 D = two doors

Other accessories

Mounting plate	Door stopper
Rain shelters	Chart pocket
19 inch rails	Mounting bracket for light
Lock	Plinth
Swing handle	Base
Eyebolts	



Customer specific sizes and solutions also available.